



SQK

Industrial Degreaser

SQK is a powerful industrial strength cleaner for big jobs. Low foaming action makes it ideal for automatic scrubbers, pressure washers, steam cleaners and mop or sponge and bucket applications. Properly diluted, it becomes an excellent spray and wipe cleaner.

DETAILED USAGE & INSTRUCTIONS

LIGHT DUTY CLEANING: Dilute SQK at 2 oz/gal of water (1:64) for damp mopping and general cleaning. Mop, spray or wipe on and wipe or rinse off as required. **NORMAL CLEANING:** Dilute SQK at 4 oz/gal of water (1:32) for cleaning of floors, walls, ventilation and air filtering systems. **HEAVY DUTY CLEANING:** Dilute PEPCO SQK at 32 oz/gal of water (1:4) on all stubborn soils on concrete floors, machinery, etc. SQK can be used through auto-scrubbers and pressure sprayer. **AUTOMATIC SCRUBBERS:** Fill solution tank and clean floors following machine manufacturer's instructions. For extreme soil build-up, make one pass over floor without engaging vacuum pick-up. Allow cleaning solution to penetrate, then go over floor with both scrubber and vacuum pick-up operating. **PRESSURE WASHERS:** Set metering mechanism to deliver desired dilution. On vertical surfaces begin spraying at lowest point and move in an upward direction until entire area is clean. Pressure rinse from top down with clear water. **STEAM CLEANING:** Set metering mechanism to deliver desired dilution. Follow machine manufacturer's cleaning instruction. **SPRAY & WIPE:** Spray soiled surface and wipe clean. Rinse with potable water. **COLD or HOT TANK CLEANING:** Soak parts for 10 minutes, longer if extremely soiled or in cold tank degreasing. Remove clean parts from tank, rinse and air dry. **WHITEWALL TIRE CLEANING:** Spray onto whitewall, scrub with stiff bristle brush and rinse with clear water. **PRECAUTION:** Do NOT allow to dry on glass — may etch. Authorized by the USDA for use in federally inspected meat and poultry plants.

RECOMMENDED USES: Ovens, Broilers and Cooking Equipment, Kitchen Floors and Food Processing Areas, Concrete Floors, Cold or Hot Tank Cleaning

Wallmount Dispensed System Operating Procedures: Turn on water source to wall mount unit. Uncap the reload cartridge. Firmly place one hand on top of the wall mount dispenser holding the cartridge from the bottom, push it up into the wall mount dispenser until the cartridge locks into place. Check that the cartridge is securely in place by pulling down gently. Turn wall mount valve to "ON" position. Fill to desired container level. **TO UNLOAD WALL MOUNT:** Make sure wall mount unit valve is in the "OFF" position. Place one hand under the existing reload cartridge and press the red "To Release Cartridge Press" button and allow the cartridge to drop down into your hand. Place the cap back on cartridge and put back into storage rack. If cartridge is empty, discard according to local, state and federal regulations. Shut off water source to wall mount unit.

The "Gun II" Dispensed System Operating Procedures: Cover or remove all food products from area. Remove gross soil from surfaces and equipment. Attach GUN II to Gilmer hose sprayer quick connect. Attach cartridge to GUN II. Apply hot foam liberally to all washable surfaces including floors, walls, tables, etc. Allow foam to cling to surface at least 5 minutes. Remove GUN II from sprayer nozzle and rinse thoroughly. Let surface drain dry. Do not wipe dry. Tilt movable surfaces to aid water run-off. To sanitize surfaces: Spray with EPA registered NO RINSE SANITIZER following directions on the container. Leave surfaces tilted until equipment is put back in use.

Refer to the product label or contact a Cynamic Chemical Co. professional for additional usage instructions.

TECHNICAL SPECIFICATIONS

Appearance / ColorClear
OdorGlycol Ether
Shelf Life2 years
Solubility in WaterComplete
FoamingNone
pH> 13.5
Specific Gravity.....1.056 +/- 0.005
Storage Temperature.....45-110 °F

FEATURES & BENEFITS

- Extra Power for the Toughest Soils
- Non-Flammable
- Dissolves Grease and Oil
- Removes Burned On Carbonized Soils

000256

CYNAMIC
CHEMICAL COMPANY

1472 Louis Bork Drive
Batavia, IL 60510